


Butées amortisseurs

Butées coniques avec vis

Type	D m/m	H m/m	Vis M	L m/m	Charge Kgs.
CV-20	20	20	M-6	18	70
CV-25	25	20	M-8	20	100
CV-306	30	30	M-6	17	150
CV-308	30	30	M-8	20	150
CV-50	50	48	M-10	25	380
*CV-50x64	50	64	M-8	35	370
CV-70	70	60	M-12	35	550
CV-90	90	74	M-16	45	1.100
CV-95	95	82	M-16	45	1.100




Dureté - 65 Shore.

* Dureté de 50 sh

Butée coniques avec trou taraudé


Type	D m/m	H m/m	Taraudage M	Charge Kg.
CT-20	20	20	M-6	70
CT-25	25	20	M-8	100
CT-306	30	30	M-6	150
CT-308	30	30	M-8	150
CT-50	50	48	M-10	380
CT-70	70	60	M-12	550
CT-90	90	74	M-16	1.100
CT-95	95	82	M-16	1.100



Dureté - 65 Shore.

Butées

Type	D m/m	H m/m	vis / taraud M	Charge Kgs.
CV-85	84	52	M-12x35	1.500
CV-120	120	75	M-16x45	3.000
CT-85	84	52	M-12	1.500
CT-120	120	75	M-16	3.000



Dureté - 65 Shore.



ENERGIE LEVAGE

10 Rue Cécile Sorel 95540 Mery sur Oise

Tél: 01 30 36 51 40 Fax: 01 77 65 62 82

Mail: info@energie-levage.fr web: www.energie-levage.fr